


# STATEMENT

I, Hiroyoshi TERAOKA, residing at Ark Mori Building 28F, 12-32, Akasaka 1-chome, Minato-ku, Tokyo 107-6028, Japan, hereby state that I have a thorough knowledge of the English and Japanese languages and that the attached document is an accurate English translation of the Japanese specification of Japanese Patent Application 2000-192735 filed June 27, 2000, upon which the present application claims a priority.

Declared at Tokyo, Japan

This 25<sup>th</sup> day of July, 2003

A handwritten signature in black ink, appearing to read 'Hiroyoshi Teraoka', written in a cursive style.

Hiroyoshi TERAOKA

PATENT OFFICE  
Japanese Government

This is to certify that the annexed is a true copy of  
the following application as filed with this office.

Date of Application: June 27, 2002

Application Number: Japanese Patent Application  
No. 2000-192735  
[JP2000-192735]

Applicant(s): TOHOKU PIONEER CORPORATION

May 13, 2003

Commissioner,

Patent Office: Shinichiro Ohta

(Seal)

Issuance No. Pat. 2003-3035602

[Name of Document] Patent Application  
[Reference Number] 54P0597  
[Submission Date] June 27, 2000  
[Addressed To] Commissioner, Patent Office  
[International Classification] H05B 33/00

[Title of the Invention] ORGANIC ELECTROLUMINESCENT  
DISPLAY PANEL

[Number of Claim(s)] 7

[Inventor]

[Address] c/o TOHOKU PIONEER CORPORATION,  
Yonezawa Works,  
4-3167-7, Hachiman-para,  
Yonezawa, Yamagata

[Name] Kenichi OKUYAMA

[Inventor]

[Address] c/o TOHOKU PIONEER CORPORATION,  
Yonezawa Works,  
4-3167-7, Hachiman-para,  
Yonezawa, Yamagata

[Name] Kenichi NAGAYAMA

[Inventor]

[Address] c/o TOHOKU PIONEER CORPORATION,  
Yonezawa Works,  
4-3167-7, Hachiman-para,  
Yonezawa, Yamagata

[Name] Toru MORITA

[Applicant for Patent]

[Identification Number] 000201926

[Appellation] TOHOKU PIONEER CORPORATION

[Name] Toru MORIYA

[Agent]

[Identification  
Number] 100079119

[Attorney]

[Name] Motohiko FUJIMURA

[Indication of Fee]

[Means of Payment] Prepayment

[Registered Number  
of Prepayment] 016469

[Amount of Payment] 21000

[List of Attached Documents]

[Article] Specification 1 copy

[Article] Drawings 1 copy

[Article] Abstract 1 copy

[General Power  
of Attorney No.] 9007281

[Designation of Document] SPECIFICATION

[Title of the Invention] ORGANIC ELECTROLUMINESCENT DISPLAY  
PANEL

[Claims]

[Claim 1] An organic electroluminescent display panel comprising:

a substrate including a display panel region that consists of a plurality of organic electroluminescent devices each composed of a plurality of display electrodes and an organic material layer, which are stacked; and

electrically conductive connecting lines electrically connected to said electrodes formed in a domain surrounding the display panel region on said substrate,

wherein said connecting lines are formed in such a way as to have lower resistance in comparison with resistance of said electrodes formed on the display panel region.

[Claim 2] The organic electroluminescent display panel according to claim 1, wherein said connecting lines are constituted by electrically conductive thick portions that are thicker in comparison with said electrodes formed on the display panel region.

[Claim 3] The organic electroluminescent display panel according to claim 1, wherein the surface area of the connecting lines is larger in comparison with that of said electrodes formed on the display panel region.

[Claim 4] The organic electroluminescent display panel according to claim 1, wherein said connecting lines are made of a material that is lower in resistance in comparison with a material of said electrodes formed on the display panel region.

[Claim 5] The organic electroluminescent display panel according to claim 2, wherein a total thickness of said connecting lines and said thick portions is larger than a film thickness of said electrode provided on a topmost surface.

[Claim 6] The organic electroluminescent display panel according to claim 1, wherein said connecting lines are made of the same material as the display electrode provided on a topmost surface, and wherein a thickness of said connecting lines is nearly equal to a film thickness of said electrode provided on the topmost surface.

[Claim 7] The organic electroluminescent display panel according to claim 2, wherein said thick portions are made of the same material as said connecting lines.

[Detailed Description of the Invention]

[0001]

[Technical Field to which the Invention Belongs]

The present invention relates to an organic electroluminescent (hereunder abbreviated as EL) display panel that has a plurality of organic EL devices, which are formed on a substrate in a predetermined pattern and each have

a light emitting layer constituted by a thin film made of an organic compound material exhibiting electroluminescence that is the emission of light resulting from current injection.

[0002]

[Prior Art]

Hitherto, there have been organic electroluminescent devices (hereunder referred to as organic EL devices) serving as display devices each using a laminated element made of an organic luminescent material.

An organic EL device is constituted by serially stacking a transparent electrode, an organic EL medium, and a metallic electrode on a transparent substrate. For example, the organic EL medium comprises a single organic light emitting layer, or comprises a three-layer medium consisting of an organic hole transport layer, an organic light emitting layer, and an organic electron transport layer, or comprises a two-layer medium consisting of an organic hole transport layer and an organic light emitting layer, or comprises a laminated medium obtained by inserting an electron or hole injecting layer into between proper ones of such layers.

[0003]

For example, an organic EL display panel of the matrix display type is constituted by serially stacking line electrodes, which include transparent electrode layer, and organic EL media, and row electrodes including metallic

electrode layers each of which intersects with a corresponding line electrode. The line electrodes are each formed like a strip, and arranged at predetermined intervals in such a way as to be parallel with one another. The row electrodes are placed in a similar manner. Thus, the display panel of the matrix display type has an image display arrangement, that is, a display panel region consisting of light emitting pixels respectively constituted by plural organic EL devices that are formed at intersections (referred to as "dots") of plural line electrodes and plural row electrodes.

[0004]

The organic EL device is of the current injection type. Thus, the luminous efficiency of the device largely depends upon reduction in the resistance of each electrode line. Therefore, when the resistance of each electrode line is high, a large voltage drop is caused by electric current flowing therethrough. Thus, inconsistencies in luminance occur on the panel. Consequently, display quality is degraded.

Thus, there is the necessity for using a low resistance material for wiring of the electrodes in the display panel region on the substrate. However, the conventional organic EL device has a drawback in that especially, the material of the transparent electrode, which serves as an anode and made of indium tin oxide (hereunder referred to as "ITO"), has a high sheet resistance.



[0005]

Thus, the resistance is reduced by using low-resistance auxiliary metallic lines for wiring between the transparent electrodes (or anodes) in the display panel region. That is, patterned anodes are stacked on the substrate. Moreover, metallic lines are stacked thereon. Thereafter, an organic material layer made of an organic compound, and cathodes are stacked thereon in sequence. Thus, the devices are formed, and moreover, each of the cathodes and the anodes is formed in such a manner as to be connected to an external terminal.

[0006]

[Problems that the Invention is to Solve]

However, the reduction in the resistance of the wires, such as connecting lines, provided outside the display panel region on the substrate is not attained.

The invention is accomplished in view of the aforementioned drawback. Accordingly, an object of the invention is to provide an organic EL device, which can reduce the resistance of electrode wires and realize high display quality, by a process that is easy to perform.

[0007]

[Means for Solving the Problems]

To achieve the foregoing object of the invention, according to the invention, there is provided an organic electroluminescent display panel that comprises a substrate

including a display panel region consisting of a plurality of organic electroluminescent devices each composed of a plurality of display electrodes and an organic material layer, which are stacked, and also comprises electrically conductive connecting lines electrically connected to the electrodes formed in a domain surrounding the display panel region on the substrate. The connecting lines are formed in such a way as to have lower resistance in comparison with the resistance of electrodes formed on the display panel region.

[0008]

In an embodiment of the organic electroluminescent display panel of the invention, the connecting lines are constituted by electrically conductive thick portions that are thicker in comparison with the electrodes formed on the display panel region.

In an embodiment of the organic electroluminescent display panel of the invention, the surface area of the connecting lines is larger in comparison with that of the electrodes formed on the display panel region.

[0009]

In an embodiment of the organic electroluminescent display panel of the invention, the connecting lines are made of a material that is lower in resistance in comparison with the material of the electrodes formed on the display panel region.

In an embodiment of the organic electroluminescent display panel of the invention, a total thickness of the connecting lines and the thick portions is larger than the film thickness of the electrode provided on a topmost surface.

[0010]

In an embodiment of the organic electroluminescent display panel of the invention, the connecting lines are made of the same material as the display electrode provided on a topmost surface. Moreover, the thickness of the connecting lines is nearly equal to the film thickness of the electrode provided on the topmost surface.

In an embodiment of the organic electroluminescent display panel of the invention, the thick portions are made of the same material as the connecting lines.

[0011]

[Mode for Carrying out the Invention]

Hereinafter, an embodiment of the invention is described with reference to the accompanying drawings.

FIG. 1 shows an organic EL display panel 42 that is an embodiment of the invention. This panel includes a display panel region 41 consisting of plural organic EL devices, and a wiring region 44 consisting of external terminals and wires, that are connected to the organic EL devices.

[0012]

The display panel region 41 is an image display

arrangement region consisting of plural light emitting pixels arranged in a matrix-like manner on a substrate 2. Each of the light emitting pixels comprises light emitting portions respectively corresponding to red light R, green light G, and blue light B. As shown in FIG. 2, in the display panel region 41, each of the light emitting portions is constituted by an organic EL medium 8 adapted to emitting corresponding color light, which is sandwiched between overlapping portions of a first electrode, which is a transparent anode line 3, and a second electrode, which is a cathode line 9 perpendicular to the first electrode. In a plan view of this figure, the first electrode and the second electrode intersect with each other at the overlapping portion. The adjacent second display electrode lines 9 are electrically separated by a partition 7, which is placed therebetween and formed on an insulating film 6, from each other. A sealing film 50 is formed on the second display electrode lines 9 and the partitions 7.

[0013]

In the wiring region 44 surrounding the display panel region 41 provided on the substrate 2, each of electrically conductive connecting lines 5 is formed in such a manner as to be electrically connected to a corresponding one of the electrodes, as shown in FIG. 1.

As illustrated in FIG. 3, electrically conductive thick portions 5a are formed on the connecting lines 5. A total

thickness of the connecting line 5 and the corresponding thick portion 5a is larger than the film thickness of at least the display electrode, that is, a cathode line 9, formed on the topmost surface of the panel. Thus, the sectional area of wires is increased, so that reduction in resistance of the wires is achieved. The connecting lines 5 are made of the same material as the display electrode, that is, the cathode line 9 provided on the topmost surface. The thickness of the connecting lines 5 is nearly equal to the film thickness of the display electrodes. This is because these constituent elements are formed by using the same deposition mask. As shown in FIG. 3, the thick portions 5a are made of the same material as the connecting lines 5, after the lines 5 are formed.

[0014]

Thus, the reduction in the resistance of the wires is achieved by forming the connecting lines in such a manner as to be constituted by electrically conductive portions that are thicker in comparison with the electrodes formed on the display panel region. Alternatively, the reduction in the resistance of the wires is achieved by forming the connecting lines so that the surface area thereof is larger in comparison with the electrodes formed on the display panel region. Further, alternatively, the effects of reduction in the resistance of the wire are obtained by forming the connecting lines from a material whose resistance is lower in comparison with that of

the electrodes formed on the display panel region.

[0015]

FIGS. 4 to 9 illustrate a process of manufacturing the organic EL display panel according to the embodiment of the invention.

First, as illustrated in FIG. 4, a substrate 2 made of a transmissive material, such as glass, is prepared. A plurality of first electrodes, that is, transparent anodes 3 for the display panel region 41, which are made of ITO and extend parallel to one another, are formed on a principal surface of the substrate 2. Simultaneously, pad portions 3P for external electrode terminal portions outside a display area 39, in which objects, such as icons, are displayed, and outside an image display arrangement area, and for connection of cathodes to be formed later are formed from ITO.

[0016]

Incidentally, the transparent anodes 3 may be provided by forming connected island-like ITO electrodes in a matrix-like manner so as to form an image display arrangement area, and by evaporating onto the ITO electrodes metallic bus electrodes, which are used for horizontally and electrically connecting the island-like ITO electrodes.

In the case of forming ITO films, connecting portions con (to be described later) for connecting the connecting lines are simultaneously formed. The first display electrodes do

not necessarily have the same shape. However, each of the first display electrodes is formed in such a way as to have the connecting portion con (to be described later).

[0017]

Next, as illustrated in FIG. 5, auxiliary electrodes 3b made of Cr are formed on the connecting portions con of the ITO display areas 39 for displaying objects, such as icons, and on the pad portions 3P for connection of the external electrode terminal portions and of the cathodes, and on anode connecting portions provided at end parts of the transparent anodes 3. These auxiliary electrodes 3b are formed by etching.

Next, as illustrated in FIG. 6, an insulating layer 6 is formed and stacked on the substrate by using, for instance, a photosensitive resin and  $\text{SiO}_2$ . The insulating layer 6 is formed on the part of the substrate, which is other than through ports having boundaries framing the dot light emitting portions of the device, that is, other than through holes or openings H, so that the first display electrodes 3 and the connecting portions con (to be described later) for connection of the connecting lines are exposed. Similarly, the substrate is coated with an insulating film except the light emitting portions and the connecting portions thereof, such as the icon display areas 39 and the connecting portions thereof, and pad portions 3P for connection of external electrode end portions and of cathode electrodes and anode connecting parts of end

portions of the transparent anodes 3 so that such light emitting portions and the connecting portions are exposed.

[0018]

Further, as illustrated in FIG. 7, plural partitions 7, which are made of a photosensitive resin and parallel to one another, are formed so that the cathodes of the second display electrodes 9 are formed at a later step in such a manner as to be separated from one another. That is, plural electrically insulating partitions 7 are formed so that parts corresponding to the dot light emitting portions of the first display electrode 3 are exposed, and that the walls 7 extend in a direction perpendicular to the first electrode and placed at predetermined intervals.

[0019]

Next, as illustrated in FIG. 8, an organic material layer 8 made of tetraphenyldiamine (TPD) and/or tris-(8-hydroxyquinolinolato)aluminum ( $\text{Alq}_3$ ). At that time, the organic material layer 8 may be formed by evaporating the material of the hole transport layer in such a way as to cover at least the entire light emitting area of the device. Needless to say, the organic material layer 8 is formed in such a manner as to keep clear of the connecting portions con of the first display electrodes.

[0020]

Next, as illustrated in FIG. 9, the second display



electrodes (that is, cathodes) 9 and the connecting lines 5 are simultaneously formed. This is performed as follows. First, for example, Al is employed as the material of the second display electrodes 9 and the connecting lines 5. Then, the second display electrodes 9 made of Al is evaporated onto and stacked on a region, in which the organic material layer 8 is formed, on each of the first display electrodes 3 by evaporating the material using a predetermined mask. Thus, the light emitting display region of the device is formed. Moreover, other portions, onto which Al is evaporated, are formed in such a way as to include the connecting lines 5. In this way, the demarcation of the light emitting portions is performed by the organic material layer at each of the overlapping portions between each of the first display electrodes and a corresponding one of the second display electrodes, each of which has a horizontal section intersecting with that of the first display electrodes. Simultaneously, the demarcation of the wiring area 44 consisting of the external terminals and wires connected to the organic EL device is performed.

[0021]

Further, in this case, a part of the connecting lines 5 are evaporated onto the connecting portions 40 that are already formed. Thus, the connecting portions 40 and the connecting lines 5 are simultaneously and electrically connected to one another.

Next, as illustrated in FIGS. 1 and 3 described above, the evaporation of metal needed still more for wiring is repeated, so that the electrically conductive thick portions 5a made of Al are formed on the connecting lines 5. Thus, the connection of wires in the display panel region 41 of the organic EL device is completed. In the case of using a mask having a pattern, in which a mask opening portion for forming the thick portions is large and slits are thin, the strength of a portion thereof in the vicinity of the opening portion is insufficient. Thus, when the thick portions 51 are formed, the plural thick portions are intermittently positioned to thereby eliminate the drawback that the mask is warped. Consequently, a fine wiring pattern is formed.

[0022]

Finally, after the second display electrodes are formed, a sealing film 50 for preventing moisture from entering the device is formed over the entire region by using an inorganic or organic material. Thus, a full-color organic EL display panel is obtained.

[0023]

[Effects of the Invention]

The panel of the invention is constructed as described above. Thus, the reduction in the resistance of connecting lines can be achieved by a simple process. Consequently, an organic EL device display panel enabled to display an image

with high display quality and without inconsistencies in the luminance can be realized.

[Brief Description of the Drawings]

[FIG. 1]

It is a partially enlarged schematic plan view of a multiple chamfered transparent substrate of an embodiment of the invention.

[FIG. 2]

It is a partially enlarged sectional view taken on line A-A of FIG. 1.

[FIG. 3]

It is a partially enlarged sectional view taken on line B-B of FIG. 1.

[FIG. 4]

It is a schematic plan view of a substrate in a process of manufacturing an organic EL display panel, which is the embodiment of the invention.

[FIG. 5]

It is a schematic plan view of the substrate in the process of manufacturing the organic EL display panel, which is the embodiment of the invention.

[FIG. 6]

It is a schematic plan view of the substrate in the process of manufacturing the organic EL display panel, which is the embodiment of the invention.

[FIG. 7]

It is a schematic plan view of the substrate in the process of manufacturing the organic EL display panel, which is the embodiment of the invention.

[FIG. 8]

It is a schematic plan view of the substrate in the process of manufacturing the organic EL display panel, which is the embodiment of the invention.

[FIG. 9]

It is a schematic plan view of the substrate in the process of manufacturing the organic EL display panel, which is the embodiment of the invention.

[Description of the Reference Numerals and Signs]


- 2 substrate
- 3 first display electrode
- 5 connecting line
- 5a thick portion
- 6 insulating material
- 8 organic material layer
- 9 second display electrode

【書類名】

図面


FIG. 1

【図1】




【図2】

FIG. 2




~~【图 3】~~

FIG. 3



~~【※4】~~

FIG. 4



【図5】

FIG. 5





FIG. 6

【図6】



【図7】

FIG. 7





FIG. 8


【図8】





【図 9】

FIG. 9



[Designation of Document] ABSTRACT

[Abstract]

[Problem] It is to provide an organic electroluminescent display panel enabled to reduce the resistance of electrode wires.

[Means for Resolution] An organic electroluminescent display panel comprises a substrate that includes a display panel region consisting of a plurality of organic electroluminescent devices each composed of a plurality of display electrodes and an organic material layer, which are stacked, and also comprises electrically conductive connecting lines electrically connected to electrodes formed in a domain surrounding the display panel region on the substrate. The connecting lines are formed in such a way as to have a lower resistance in comparison with the resistance of electrodes formed on the display panel region.

[Selected Drawing] FIG. 1